Z10MK3 KU-BAND COMMUNICATION

The SuperTrack Z-Series is the perfect solution for ships looking for broadband speeds at sea. Stay in touch with your networks via high speed access to the internet, email, multiple VoIP phones and more.





STANDARD FEATURES

- Built in Wire Rope Isolator & Shock Absorber
- Automatic Satellite Search & Skew Control
- Unlimited Azimuth Uninterrupted searching keep you in business however you ship turns Cable wrap free
- Brake System
- Accurate Signal Acquisition by KNS's Distinctive Algorithm
- Pre-programmed Satellite Database Editable 80 satellite data
- Antenna Control Unit 3 Types of Gyro Input (NMEA, Synchro, Step by Step)
- CE R&TTE Certified
- Intelsat Qualified

ABOVE DECK

Dish Diameter Antenna Dimension

Antenna Weight Radome Material

Frequency

Antenna Gain

G/T

Operating Platform LNB

BUC

Skew Control Elevation Angle Azimuth Range Cross Angle

Ship Motion

Tracking Speed

Vibration Damper

Humidity **Antenna Input Power** 100cm(40")

144cm(D) x 152cm(H)

119.5 Ka

Honeycomb FRP

TX: 13.75 ~ 14.5 GHz RX: 10.7 ~ 12.75 GHz

TX: 41.0 dBi @ 14.25 GHz

RX: 40 dBi @ 11.75 GHz 18.89 dB/K (in Radome)

@ 30deg. Elevation angle and 11.75GHz, Clear Sky

3 - Axis

Single PLL LNB / Universal LNB(optional) 4W / 6W / 8W / 16W / 25W / 40W(optional)

Automatic -18° to +110° Unlimited $+35^{\circ}$

Roll: ±24° at 8-12 sec periods

Pitch: ±14° at 6-12 sec periods Yaw: ±8° at 15-20 sec periods

More than 90°/sec

Shock Absorber, Rubber Damper

and Wire Rope Isolator

Temperature -20°C to +55°C Up to 100% @ 40°C 48V DC, 4.18A

BELOW DECK

ACU Size

Gyro Interface

Input Power

Output Power External I/O

19" Rack 1U size

NMEA 0183, Synchro, Step by Step 100~120V AC / 200~240V AC.

50/60Hz, 8A/4A

48V DC, 4.18A

RS-232C, Mini-USB, Ethernet, Console

PACKING

Size

Gross Weight Packed by

Certification/ Qualification

158 x 158 x 177 cm

247Kg

Wooden Crate

MIL-STD-167 MIL-STD-461 MIL-STD-901

WARRANTY INFORMATION

KNS offers 3-year parts, 1-year onboard labour warranty for the SuperTrack series

^{*} This Specification can be changed without notice.

